

EKF 464 P

Available version with right hinged door mod. EKF 464 AL P



ELECTRIC CONVECTION OVEN WITH MANUAL CONTROL

A versatile and functional oven with limited dimensions and capacity of four trays 600x400 mm. An effective tool for baking bread, pastries and small cakes.



DIMENSIONAL FEATURES

Oven dimensions (WxDxH mm)	784	774	634
Oven weight (kg)	51,2		
Distance between rack rails (mm)	83		

ELECTRICAL FEATURES

Power supply (kW)	6,2
Frequency (Hz)	50 (60 on demand)
Voltage (Volt)	AC 380/400 2N
N° of motors	1 Bidirectional
Boiler	/
Protection against water	IPX3

EQUIPMENT

Cardboard box dimensions with pallet (WxDxH mm)	805	830	800
Lateral supports	1 right + 1 left		
Cable	Two-Phase + neutral [5G 2,5] - L=1600 mm		

PLUS

Door with inspectionable glass
Stainless steel cooking chamber
Embedded gasket
IPX 3
CB certification
Quick fastening of lateral supports
Stackable
Forced cooling system of inner parts
New design of cooking chamber
New design of handle

FUNCTIONAL FEATURES

Power	Electricity
Capacity	N° 4 Trays (600x400 mm)
Type of cooking	Ventilated
Humidification	/
Cooking chamber	AISI 430 Stainless Steel
Temperature	50 ÷ 260°C
Temperature control	Thermostat
Control panel	Electromechanic - Lower side
N° of programs	/
Programmable cooking steps	/
Pre-heating temperature	/
Pre-heating function	/
Door	Tilt door Ventilated Inspectionable glass
Modularity	Available

OPTIONAL

Aluminium tray (600x400x20 mm)	Cod. KT9P/A
Perforated aluminium tray (600x400x20 mm)	Cod. KTF8P/A
5 Lanes perforated aluminium tray (600x400x20 mm)	Cod. KTF9P
Chromed grid (600x400 mm)	Cod. KG9P
5 Lanes AISI 304 grid (600x400 mm)	Cod. KG5CPX
Proofer	Cod. EKL 864 Cod. EKL 864 R
Table	Cod. EKT 411 Cod. EKTR 411 Cod. EKTS 411 Cod. EKTRS 411 Cod. EKT 411 D
Air reducer	Cod. EKRPA/A
Possibility of bivalent supports	Code EKF 416 P and EKF 416 AL P (with side door opening)
Kit for overlapping ovens	Cod. EKKM4

